

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-13. (Canceled)

14. (Currently Amended) A method [[in an apparatus]] for wireless communications comprising:

receiving, by [[the]] an apparatus, from a single remote station a reverse link signal that comprises a plurality of subchannel signals;

comparing a frame error rate of each of said subchannel signals with a frame error rate threshold; and

generating power control messages, based on the comparison, to be used to independently adjust transmit powers of more than one of said plurality of subchannel signals to different levels.

15-16. (Canceled)

17. (Previously Presented) The method as recited in claim 14 further comprising:
generating a plurality of quality threshold values, corresponding to said plurality of subchannels, in accordance with a measured frame error rate for each of said subchannel signals.

18. (Previously Presented) The method as recited in claim 14 wherein said generating includes generating at least a plurality of bits, wherein each bit represents a command to increase or decrease the transmit power of one of said subchannel signals by a predetermined amount.

19. (Previously Presented) The method as recited in claim 14 further comprising:
generating a plurality of gain values; and
applying each gain value to one of said plurality of subchannel signals for adjusting the transmit powers of said subchannel signals.

20. (Previously Presented) The method as recited in claim 14 further comprising:
decoding each of said corresponding subchannel signals and determining frame errors in
said subchannel signals.

21. (Previously Presented) An apparatus for wireless communication comprising:
a receiver configured to receive from a single remote station a reverse link signal that
comprises a plurality of subchannel signals;
a threshold generator configured to provide a frame error rate threshold for at least one of
the subchannel signals;
a comparator configured to compare a frame error rate of at least one of the subchannel
signals with the threshold for that subchannel signal; and
a message generator configured to generate power control messages, based on the
comparison, to be used to independently adjust transmit powers of more than one of the plurality
of subchannel signals to different levels.

22. (Previously Presented) The apparatus for wireless communication of claim 21
wherein the message generator is configured to generate a plurality of quality threshold values,
corresponding to the plurality of subchannels, in accordance with a measured frame error rate for
each of the subchannel signals.

23. (Previously Presented) The apparatus for wireless communication of claim 21
wherein the message generator is configured to generate at least a plurality of bits, wherein each
bit represents a command to increase or decrease the transmit power of one of the subchannel
signals by a predetermined amount.

24. (Previously Presented) The apparatus for wireless communication of claim 21
further comprising: a decoder configured to decode each of the subchannel signals from the
received reverse link signal; and
wherein the comparator is configured to calculate the frame error rate in each of the
subchannel signals.

25. (Previously Presented) An apparatus for wireless communication comprising:
means for receiving from a single remote station a reverse link signal that comprises a

plurality of subchannel signals; means for providing a frame error rate threshold for at least one of the subchannel signals;

means for comparing a frame error rate of at least one of the subchannel signals with the threshold for that subchannel signal; and

means for generating power control messages, based on the comparison, to be used to independently adjust transmit powers of more than one of the plurality of subchannel signals to different levels.

26. (Previously Presented) The apparatus for wireless communication of claim 25 further comprising means for generating a plurality of quality threshold values, corresponding to the plurality of subchannels, in accordance with a measured frame error rate for each of the subchannel signals.

27. (Previously Presented) The apparatus for wireless communication of claim 25 further comprising means for generating at least a plurality of bits, wherein each bit represents a command to increase or decrease the transmit power of one of the subchannel signals by a predetermined amount.

28. (Previously Presented) The apparatus for wireless communication of claim 25 further comprising means for decoding each of the subchannel signals from the received reverse link signal; and means for calculating the frame error rate in each of the subchannel signals.

29. (Previously Presented) A base station comprising:
an antenna;
a receiver configured to receive from a single remote station, via the antenna, a reverse link signal that comprises a plurality of subchannel signals;
a threshold generator configured to provide a frame error rate threshold for at least one of the subchannel signals;
a comparator configured to compare a frame error rate of at least one of the subchannel signals with the threshold for that subchannel signal; and
a message generator configured to generate power control messages, based on the comparison, to be use to independently adjust transmit powers of more than one of the plurality of subchannel signals to different levels.